

# Pyramid Series Proximity™ Readers

## Models P-600 Rocky Proximity Reader & Keypad and P-650 Card + PIN Proximity Reader & Keypad

- Industry First - Combines a Pyramid Series Reader with the Essex Stainless Steel Keypad
- Industry standard Wiegand outputs on the reader and keypad for compatibility with virtually any access system
- Innovative weather and vandal resistant package
- Available in several colors
- Scratch resistant finish



Intended for higher security applications, the **P-600 Rocky Proximity Reader and Keypad** and **P-650 Card + PIN Proximity Reader** are members of Keri's **Pyramid Series Proximity** line of readers, cards, and tags featuring optional HID compatibility. An industry first, it is one of the most innovative access control products available, combining both an Essex stainless steel keypad and a Pyramid Series Proximity reader into a single package.

The P-600 and P-650 are ideal for those applications that require both an access credential and a personal identification number (PIN). Compatible with most manufacturers' access control systems, the reader portion of the P-600 outputs data in industry standard pass-through Wiegand data formats. Sharing the data lines with the reader, the keypad portion of the P-600 can be formatted to transmit data in either of two standard Wiegand data formats, 8-Bit Burst and 26-Bit Wiegand. The P-650 is a special version designed for use with Keri's **PXL-250W Tiger Controller** to provide card + PIN dual verification capability based on a pre-assigned PIN for each 26 bit card number. The P-600 and P-650 include a four-state LED (red, green, amber and off) and audio tone. They have several built in diagnostic functions including a start up self-check and data line test. Additionally they are available in black and off-white, allowing the P-600 and P-650 to match virtually any office décor.

The single-piece P-600 and P-650 deliver read ranges up to 4 inches and operates from 5 to 14 VDC at a nominal current draw of 90 mA, allowing for flexibility in the use of power supplies. In most cases it can be powered directly from the access control panel. The electronics are sealed in epoxy potting, making the readers both vandal and weather resistant. Size is 3.9 x 4.4 x 0.95 inches (99 x 112 x 24mm). Its small package size with a distinctive profile makes it a much more attractive reader to install in the workplace than other proximity reader and keypad combinations on the market.

A complete line of access credentials that may be used interchangeably with any Pyramid Series Proximity Reader complement the P-600 and P-650. These credentials include the **PSC-1 Light Proximity Card** featuring a lifetime warranty, the dye sublimation printable ISO-thin **PSM-2 Multi-Technology Proximity Card** available with a magnetic stripe, and one of the smallest, most durable credentials available, the **PSK-3 Proximity Key Ring Tag**.



1530 Old Oakland Road, Suite 100  
San Jose, CA 95112 USA  
(800) 260-5265 • (408) 451-2520 • Fax (408) 441-0309  
e-mail: sales@kerisys.com web: www.kerisys.com

DATA SHEET

Pyramid Series  
Proximity Readers

